

Base data

Code: FR 502
Description: Limit switch with one-way roller

General characteristics

Housing: Polymer housing, one threaded PG 13,5 conduit entry.
Protection degree: IP67 according to EN 60529.
Contact block: 1NO+1NC fast action
Positive opening: Yes

**Markings and quality marks**

[EAC Certificate](#)
[IMQ-UNI Certificate](#)
[CCC Certificate](#)
[CE Certificate](#)
[cULus Certificate](#)
[IMQ Certificate](#)

Documentation

Hauptkatalog: [ZE_GCP01A15-DEU_59-70.pdf \(1758 KB\)](#)
General Catalog: [ZE_GCP01A15-ENG_59-70.pdf \(3842 KB\)](#)
Catalogue Général: [ZE_GCP01A15-FRA_59-70.pdf \(3845 KB\)](#)
Catalogo Generale: [ZE_GCP01A15-ITA_59-70.pdf \(3872 KB\)](#)
2D file: [ZF_DXF_FR_x02_A10.zip \(44 KB\)](#)
3D File: [ZF_STEP_FR_x02_A10.zip \(262 KB\)](#)
Article Data Sheet: [Create Data Sheet](#)

Any information or application example, included the connection diagrams, described in this document are to be intended as purely descriptive. The choice and application of the products in conformity with the Standards, in order to avoid damages to persons or goods, is under the responsibility of the user. The drawings and data contained in this catalog are not binding, and we reserve the right to improve the quality of our products to modify them at any time without prior notification. This publication cannot be copied in whole or in part without prior permission from the publisher.

All rights reserved. © 2015 Copyright Pizzato Elettrica