





## Main

|   |   |
|---|---|
| Range of product                            | TeSys D   |
| Product or component type                   | Contacteur  |
| Device short name                           | LC1D  |
| Contacteur application                      | Motor control<br>Resistive load   |
| Utilisation category                        | AC-1<br>AC-3  |
| Poles description                           | 3P  |
| Power pole contact composition              | 3 NO  |
| [Ue] rated operational voltage              | <= 300 V DC for power circuit<br><= 690 V AC 25...400 Hz for power circuit  |
| [Ie] rated operational current              | 65 A (<= 60 °C) at <= 440 V AC AC-3 for power circuit<br>80 A (<= 60 °C) at <= 440 V AC AC-1 for power circuit  |
| Motor power kW                              | 37 kW at 660...690 V AC 50/60 Hz<br>37 kW at 500 V AC 50/60 Hz<br>30 kW at 380...400 V AC 50/60 Hz<br>18.5 kW at 220...230 V AC 50/60 Hz  |
| Motor power HP (UL / CSA)                   | 50 hp at 575/600 V AC 50/60 Hz for 3 phases motors<br>20 hp at 230/240 V AC 50/60 Hz for 3 phases motors<br>20 hp at 200/208 V AC 50/60 Hz for 3 phases motors<br>10 hp at 230/240 V AC 50/60 Hz for 1 phase motors<br>5 hp at 115 V AC 50/60 Hz for 1 phase motors<br>40 hp at 460/480 V AC 50/60 Hz for 3 phases motors |
| Control circuit type                        | AC 50/60 Hz   |
| Control circuit voltage                     | 220 V AC 50/60 Hz   |
| Auxiliary contact composition               | 1 NO + 1 NC   |
| [Uimp] rated impulse withstand voltage      | 6 kV conforming to IEC 60947  |
| Overvoltage category                        | III   |
| [Ith] conventional free air thermal current | 80 A at <= 60 °C for power circuit<br>10 A at <= 60 °C for signalling circuit   |
| Irms rated making capacity                  | 1000 A at 440 V for power circuit conforming to IEC 60947<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>140 A AC for signalling circuit conforming to IEC 60947-5-1   |
| Rated breaking capacity                     | 1000 A at 440 V for power circuit conforming to IEC 60947   |
| [Icw] rated short-time withstand current    | 260 A <= 40 °C 1 min power circuit<br>110 A <= 40 °C 10 min power circuit<br>900 A <= 40 °C 1 s power circuit<br>520 A <= 40 °C 10 s power circuit<br>140 A 100 ms signalling circuit<br>120 A 500 ms signalling circuit<br>100 A 1 s signalling circuit  |
| Associated fuse rating                      | 125 A gG at <= 690 V coordination type 2 for power circuit<br>125 A gG at <= 690 V coordination type 1 for power circuit<br>10 A gG for signalling circuit conforming to IEC 60947-5-1  |
| Average impedance                           | 1.50 mOhm at 50 Hz - Ith 80 A for power circuit   |

|                               |  |
|-------------------------------|--|
| [Ui] rated insulation voltage | 600 V for signalling circuit certifications UL<br>600 V for signalling circuit certifications CSA<br>690 V for signalling circuit conforming to IEC 60947-1<br>600 V for power circuit certifications UL<br>600 V for power circuit certifications CSA<br>690 V for power circuit conforming to IEC 60947-4-1  |
| Electrical durability         | 1.45 Mcycles 65 A AC-3 at $U_e \leq 440$ V<br>1.4 Mcycles 80 A AC-1 at $U_e \leq 440$ V  |
| Power dissipation per pole    | 6.3 W AC-3<br>9.6 W AC-1   |
| Safety cover                  | With   |
| Mounting support              | Plate<br>Rail  |
| Standards                     | EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508<br>CSA C22.2 No 14  |
| Product certifications        | CCC<br>CSA<br>GOST<br>UL   |
| Connections - terminals       | Control circuit: screw clamp terminals 2 cable(s)<br>1...4 mm <sup>2</sup> - cable stiffness: solid - without cable end<br>Control circuit: screw clamp terminals 1 cable(s)<br>1...4 mm <sup>2</sup> - cable stiffness: solid - without cable end<br>Control circuit: screw clamp terminals 2 cable(s)<br>1...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end<br>Control circuit: screw clamp terminals 1 cable(s)<br>1...4 mm <sup>2</sup> - cable stiffness: flexible - with cable end<br>Control circuit: screw clamp terminals 2 cable(s)<br>1...4 mm <sup>2</sup> - cable stiffness: flexible - without cable end<br>Control circuit: screw clamp terminals 1 cable(s)<br>1...4 mm <sup>2</sup> - cable stiffness: flexible - without cable end<br>Power circuit: EverLink BTR screw connectors 2 cable(s) 1...25 mm <sup>2</sup> - cable stiffness: solid - without cable end<br>Power circuit: EverLink BTR screw connectors 1 cable(s) 1...35 mm <sup>2</sup> - cable stiffness: solid - without cable end<br>Power circuit: EverLink BTR screw connectors 2 cable(s) 1...25 mm <sup>2</sup> - cable stiffness: flexible - with cable end<br>Power circuit: EverLink BTR screw connectors 1 cable(s) 1...35 mm <sup>2</sup> - cable stiffness: flexible - with cable end<br>Power circuit: EverLink BTR screw connectors 2 cable(s) 1...25 mm <sup>2</sup> - cable stiffness: flexible - without cable end<br>Power circuit: EverLink BTR screw connectors 1 cable(s) 1...35 mm <sup>2</sup> - cable stiffness: flexible - without cable end |
| Tightening torque             | Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Power circuit: 8 N.m - on EverLink BTR screw connectors - cable 25...35 mm <sup>2</sup> hexagonal 4 mm<br>Power circuit: 5 N.m - on EverLink BTR screw connectors - cable $\leq 25$ mm <sup>2</sup> hexagonal 4 mm  |
| Operating time                | 12...26 ms closing<br>4...19 ms opening  |
| Safety reliability level      | B10d = 2000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1<br>B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1  |
| Mechanical durability         | 6 Mcycles  |
| Operating rate                | 3600 cyc/h at $\leq 60$ °C   |

## Complementary

|                                 |  |
|---------------------------------|--|
| Coil technology                 | Without built-in suppressor module   |
| Control circuit voltage limits  | 0.85...1.1 Uc at 60 °C operational 60 Hz<br>0.8...1.1 Uc at 60 °C operational 50 Hz<br>0.3...0.6 Uc at 60 °C drop-out 50/60 Hz |
| Inrush power in VA              | 160 VA at 20 °C (cos $\phi$ 0.75) 50 Hz<br>140 VA at 20 °C (cos $\phi$ 0.75) 60 Hz   |
| Hold-in power consumption in VA | 15 VA at 20 °C (cos $\phi$ 0.3) 50 Hz<br>13 VA at 20 °C (cos $\phi$ 0.3) 60 Hz   |
| Heat dissipation                | 4...5 W at 50/60 Hz  |
| Auxiliary contacts type         | Type mirror contact (1 NC) conforming to IEC 60947-4-1<br>Type mechanically linked (1 NO + 1 NC) conforming to IEC 60947-5-1   |
| Signalling circuit frequency    | 25...400 Hz  |
| Minimum switching current       | 5 mA for signalling circuit  |
| Minimum switching voltage       | 17 V for signalling circuit  |
| Non-overlap time                | 1.5 ms on energisation (between NC and NO contact)<br>1.5 ms on de-energisation (between NC and NO contact)                    |
| Insulation resistance           | > 10 MOhm for signalling circuit   |

## Environment

|   |  |
|---|--|
| IP degree of protection                               | IP2x front face conforming to IEC 60529  |
| Protective treatment                                  | TH conforming to IEC 60068-2-30  |
| Pollution degree                                      | 3  |
| Ambient air temperature for operation                 | -5...60 °C   |
| Ambient air temperature for storage                   | -60...80 °C  |
| Permissible ambient air temperature around the device | -40...70 °C at Uc  |
| Operating altitude                                    | 3000 m without derating in temperature   |
| Fire resistance                                       | 850 °C conforming to IEC 60695-2-1   |
| Flame retardance                                      | V1 conforming to UL 94   |
| Mechanical robustness                                 | Shocks contactor closed 15 Gn for 11 ms<br>Shocks contactor open 10 Gn for 11 ms<br>Vibrations contactor closed 4 Gn, 5...300 Hz<br>Vibrations contactor open 2 Gn, 5...300 Hz |
| Height  | 122 mm   |
| Width   | 55 mm  |
| Depth   | 120 mm   |
| Product weight  | 0.86 kg  |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS                             | Compliant - since 0001 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations   |

## Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|