



SIMATIC S7-1200,
DIGITAL OUTPUT SM 1222, 16 DO, 24V DC,
TRANSISTOR 0.5A

| Supply voltage | |
|---|--------------------------------|
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| Input current | |
| from backplane bus 5 V DC, max. | 140 mA |
| Power losses | |
| Power loss, typ. | 2.5 W |
| Digital inputs | |
| Number/binary inputs | 0 |
| Digital outputs | |
| Number/binary outputs | 16 |
| In groups of | 1 |
| Functionality/short-circuit strength | No ; to be provided externally |
| Limitation of inductive shutdown voltage to | typ. (L+) -48 V |
| Switching capacity of the outputs | |
| with resistive load, max. | 0.5 A |
| on lamp load, max. | 5 W |
| Output voltage | |

| | |
|---|---------------------------|
| Rated value (DC) | 24 V |
| for signal "0", max. | 0.1 V ; with 10 kOhm load |
| for signal "1", min. | 20 V DC |
| Output current | |
| for signal "1" rated value | 0.5 A |
| for signal "0" residual current, max. | 10 µA |
| Output delay with resistive load | |
| "0" to "1", max. | 50 µs |
| "1" to "0", max. | 200 µs |
| Aggregate current of outputs (per group) | |
| horizontal installation | |
| up to 50 °C, max. | 8 A ; Current per mass |
| Relay outputs | |
| Switching capacity of contacts | |
| with inductive load, max. | 0.5 A |
| on lamp load, max. | 5 W |
| Switching frequency/contacts/at ohmic load/maximum | 0.5 A |
| Cable length | |
| Cable length, shielded, max. | 500 m |
| Cable length unshielded, max. | 150 m |
| Interrupts/diagnostics/status information | |
| Alarms | |
| Alarms | Yes |
| Diagnostic alarm | Yes |
| Diagnostic messages | |
| Diagnostic functions | Yes |
| Diagnostics indication LED | |
| For status of the outputs | Yes |
| for maintenance | Yes |
| Status indicator digital output (green) | Yes |
| Galvanic isolation | |
| Galvanic isolation digital outputs | |
| between the channels, in groups of | 1 |
| between the channels and the backplane bus | 500 V AC |
| Degree and class of protection | |
| IP20 | Yes |
| Standards, approvals, certificates | |
| CE mark | Yes |

| | |
|---|---|
| C-TICK | Yes |
| FM approval | Yes |
| Climatic and mechanical conditions for storage and transport | |
| Climatic conditions for storage and transport | |
| Free fall | |
| Drop height, max. (in packaging) | 0.3 m ; five times, in dispatch package |
| Temperature | |
| Permissible temperature range | -40 °C to +70 °C |
| Air pressure acc. to IEC 60068-2-13 | |
| Permissible air pressure | 1080 to 660 hPa |
| Mechanical and climatic conditions during operation | |
| Climatic conditions in operation | |
| Temperature | |
| Permissible temperature range | 0 °C to 55 °C horizontal mounting 0 °C to 45 °C vertical mounting 95% non-condensing humidity |
| Permissible temperature change | 5°C to 55°C, 3°C / minute |
| Connection method | |
| required front connector | Yes |
| Mechanics/material | |
| Type of housing (front) | |
| Plastic | Yes |
| Dimensions | |
| Width | 45 mm |
| Height | 100 mm |
| Depth | 75 mm |
| Weight | |
| Weight, approx. | 220 g |
| Status | Feb 21, 2013 |