



Main

Circuit breaker application	Distribution
Range of product	IK60
Device short name	IK60N
Poles description	3P
Number of protected poles	3
[In] rated current	16 A
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Utilisation category	Category A EN 60947-2 Category A IEC 60947-2
Suitability for isolation	Yes EN 60898-1 Yes IEC 60898-1

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	400 V AC 50/60 Hz
Magnetic tripping limit	5...10 x In
Breaking capacity	6000 A Icn EN 60898-1 400 V AC 50/60 Hz 6000 A Icn IEC 60898-1 400 V AC 50/60 Hz
Limitation class	3 EN 60898-1 3 IEC 60898-1
[Ui] rated insulation voltage	400 V AC 50/60 Hz EN 60898-1 400 V AC 50/60 Hz IEC 60898-1
[Uimp] rated impulse withstand voltage	4 kV EN 60898-1 4 kV IEC 60898-1
Contact position indicator	No
Control type	Toggle
Local signalling	Without
Mounting mode	Removable comb busbar installed
Mounting support	DIN rail
9 mm pitches	6
Width	54 mm
Colour	White
Connections - terminals	Tunnel type terminals top or bottom 1...25 mm ² solid 1 Tunnel type terminals top or bottom 0.5...16 mm ² flexible with cable end 1 Tunnel type terminals top or bottom 0.5...16 mm ² flexible without cable end 1 Tunnel type terminals top or bottom 1.5 mm ² flexible without cable end 1...5 Tunnel type terminals top or bottom 1.5 mm ² solid 1...5 Tunnel type terminals top or bottom 2.5 mm ² flexible without cable end 1...3 Tunnel type terminals top or bottom 2.5 mm ² solid 1...3
Wire stripping length	14 mm top or bottom
Tightening torque	2 nm top or bottom
Earth-leakage protection	Without

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	EN 60898-1 IEC 60898-1
IP degree of protection	IP3 EN 60947-2 IP3 IEC 60947-2
Pollution degree	2 IEC 60898-1 2 EN 60898-1
Electrical shock protection class	Class II front face
Tropicalisation	2 EN/IEC 60068-2-78
Relative humidity	95 %
Operating altitude	0...2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C