

# SIEMENS

## Product data sheet

**6SE6420-2UC24-0CA1**

product name

Micromaster 4



MICROMASTER 4 Familie

MICROMASTER 420 UNFILTERED 3AC 200-240V  
 +10/-10% 47-63HZ CONSTANT TORQUE POWER 4  
 KW OVERLOAD 150% FOR 60S VARIABLE  
 TORQUE POWER 4 KW 245 X 185 X 195 (H X W X  
 D) PROTECTION IP20 AMBIENT TEMP -10 TO +50  
 DEG C W/O AOP/BOP

Input voltage	230 V
Output voltage / maximum	240 V
Output voltage / minimum	0 V
<b>Line frequency rated value 50 Hz</b>	-
<b>Line frequency rated value 60 Hz</b>	-
power factor	0.95
Efficiency eta	96
<b>Pulse rate factory setting</b>	-
Design	C
Protection class IP	MICROMASTER 440
Environmental conditions / Ambient temperature in operation	-10° to +50°C
filter / [nicht versorgt - Klasse A] / [nicht versorgt - 1AC]	FALSE
type / of control	FCC, Linear - V/f

---

Height	0.245 m
Width	0.185 m
Depth	0.195 m
weight	4.8 kg
<b>letzte Änderung:</b>	Dec 31, 2012